



Specifications Noxion LED Panel Delta Value V5 28W 3920lm - 830-840 CCT | 120x30cm - UGR<19 - Backlit

[View Product](#)

General Information

|                          |                                                                                            |
|--------------------------|--------------------------------------------------------------------------------------------|
| SKU                      | 252936                                                                                     |
| EAN                      | 8719157058704                                                                              |
| Manufacturer Code        | 8719157058704                                                                              |
| Brand                    | Noxion                                                                                     |
| Manufacturer Name        | Noxion LED Panel Delta Value V5.1 28W 3920lm 2CCT 300*1200 (Philips Driver) UGR<19 Backlit |
| Any Lamp all-in warranty | 6 Years                                                                                    |
| Average Lifetime (h)     | 90000                                                                                      |
| Series                   | Delta Value                                                                                |

Technical Information

|                             |                                  |
|-----------------------------|----------------------------------|
| Technology                  | LED Integrated                   |
| Replaces (Watt)             | 2x36                             |
| Wattage                     | 28W                              |
| Voltage (V)                 | 220-240                          |
| Dimmable                    | Not Dimmable                     |
| Colour Code                 | 830 Warm White, 840 Cool White   |
| Colour temperature (Kelvin) | 3000 Warm White, 4000 Cool White |
| Colour Rendering (Ra)       | 80-89                            |
| Colour of Light             | White                            |
| Light colour options        | CCT                              |

|                          |                   |
|--------------------------|-------------------|
| Luminous Flux (Lumen)    | 3920lm            |
| Luminous Efficacy (lm/W) | 140               |
| IP-rating                | IP20              |
| Impact Protection (IK)   | IK02 - 0.20 joule |
| Fixture Connection       | Push Terminal     |
| Finish of Reflector      | Frosted           |
| Power factor             | >0.90             |
| Product Type Category    | LED Panel         |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PS (Polystyrene)               |
| Operating Temperature | -20 to +40                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | Steel                          |

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 120x30cm |
| Length (mm)    | 1195     |
| Width (mm)     | 295      |
| Height (mm)    | 32       |

 **Sensor Information** Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor



**Easy** return process